



WHEEL REBUILDING

All wheel types

* 48 h in working days, transport time excluded.

Built in France • Fast turnaround • Simplicity

VELOX
L'UNIVERS DU VÉLO

reparemaroue.fr

Customer details

Shop name *

Surname *

First name *

Telephone *

E-mail

Billing address

Delivery address

Wheel specification

Hole count (J-bend spokes only)

☐ 32T

☐ 36T

Use

☐ Road

☐ City

☐ MTB

☐ Cargo / Longtail

☐ Gravel

☐ Trekking

☐ E-bike city

☐ E-MTB

Wheel diameter

☐ 20"
ETRTO 406

☐ 24"
ETRTO 507

☐ 26"
ETRTO 559

☐ 27.5"
ETRTO 584

☐ 28/29"/700
ETRTO 622

Rim tape (optional)

☐ No

☐ Yes
Velox 120 psi

Rim width (internal, between the hooks — 27C / 30C / 35C optional)

☐ 13C

☐ 15C

☐ 17C

☐ 19C

☐ 21C

☐ 23C

☐ 25C

☐ 27C

☐ 30C

☐ 35C

Brake type

☐ V-brake

☐ Disc

☐ Rollerbrake

Rim colour

☐ Silver

☐ Black

Spoke colour

☐ Silver

☐ Black

Hub spacing (measured between the fork or frame dropouts)

Front wheel ☐ 100 mm ☐ 110 mm

TO BE FILLED IN

Rear wheel ☐ 110 mm ☐ 118 mm ☐ 119 mm ☐ 130 mm ☐ 135 mm ☐ 141 mm ☐ 142 mm ☐ 148 mm ☐ Other

Comments

Shipping address

VELOX / JMR Express

RETOUR MOYEU

13 rue de la Peltière

35130 La Guerche-de-Bretagne

France

Enclose this printed sheet in the parcel.

READ BEFORE SENDING

- Aluminium wheel, J-bend spokes (no carbon, no straight-pull).
- Send the hub alone: a complete or partly stripped wheel means a dismantling charge on top.
- Pack the hub with care: a suitable box, polystyrene padding preferred.
- Outbound shipping at your expense; return included (Chronopost).

☐ Parcel insurance 500 € — 6 € excl. VAT (tick to subscribe)

Read and approved (customer's date and signature)